

AMENDMENTS TO THE CLAIMS:

Please amend claims 1, 5 and 9 as follows:

1. (Currently Amended) Disc brake for a heavy vehicle having an axle pressure between 6 and 14 tons, comprising a disc-shaped rotor (8) consisting of a cast iron alloy and having a radius R and a caliper (32) supporting a brake lining (32) which is intended to be pressed against said rotor (8) during braking, in which said rotor (8) and brake lining (32) are arranged to absorb a brake power corresponding to a braking torque between 12 and 25 kNm and in which said brake lining (32) has a radial extent B, characterized in that the ratio B/R between the radial extent B of the lining (32) and the radius R of the rotor (8) is less than 0.38 and thereby substantially limiting a number of band shaped wear modes.

2. (Previously Presented) Disc brake according to Claim 1, characterized in that said brake lining (32) is designed to absorb a brake power corresponding to a braking torque from about 16 kNm, wherein said brake lining (32) has a radial extent of less than 70mm, to about 25 kNm, wherein said brake lining (32) has a radial extent of less than 80 mm.

3. - 4. (Cancelled)

5. (Currently Amended) Disc brake according to Claim 2, characterized in ~~25~~ that said rotor (8) is of substantially symmetrical configuration with respect to a plane running at right angles through the rotational axis and has a central bushing (12) intended for fastening to a wheel axle (6), the wear surfaces of the brake disc remaining flat when heated.

6. (Previously Presented) Disc brake according to Claim 2, characterized in that the radius of the rotor (8) is greater than 185 mm.

7. (Previously Presented) Disc brake according to Claim 2, characterized in that the brake lining (32) is configured having a tangential modulus of elasticity E greater than 400 Mpa at a contact pressure of 2 MPa at room temperature.
8. (Previously Presented) Disc brake according to Claim 2, characterized in that said caliper (30) supports two brake cylinders which are meant to press the brake lining against the rotor.
9. (Currently Amended) Vehicle having an axle pressure between 6 and 14 tons, comprising a disc brake having a disc-shaped rotor (8), consisting of a cast iron alloy and having a radius R , and a caliper (30) supporting a brake lining (32) which is intended to be pressed against said rotor (32) during braking, in which said brake lining (32) has a radial extent B , characterized in that the ratio B/R between the radial extent B of the lining (32) and the radius R of the rotor (8) is less than 0.38 and thereby substantially limiting a number of band shaped wear modes.
10. (Previously Presented) Vehicle according to Claim 9, characterized in that said axle pressure amounts to between 11 and 14 tons and in that said brake lining (32) has a radial extent of less than 80 mm.
11. (Previously Presented) Vehicle according to Claim 9, characterized in that said axle pressure amounts to between 8.5 and 11 tons and in that said brake lining (32) has a radial extent of less than 75 mm.
12. (Previously presented) Vehicle according to Claim 9, characterized in that said axle pressure amounts to between 6 and 8.5 tons and in that said brake lining (32) has a radial extent of less than 70 mm.